ORDER FORM



ORDER e: rooforde	ers@wendland.uk.com	PLEASE SKETCH Y	OUR PREFERRED D	
	ers@wendland.uk.com	- mark window, door	& wall positions/type:	
New Build	Replacement Project	DIMENSIONS	Internal frame to in	ternal frame
		ROOF U-VALUE:	0.15 (standard)	0.12 (thermally enhanced)
ACCOUNT No.		PLAN VIEW		
Company Name				
Order Number				
JOB REFERENCE				
Installer Company Name	e			
Company Contact				
Telephone No.				
Email				
Delivery Address		FRONT ELEVATION		
		FRONTELEVATION		
POSTCODE				
Delivery Date Req				
Quotation Ref				
CRITICAL INFORMATIC *Required for structura				
Site Postcode				
Roof Pitch				
CUSTOMER NOTE: Please of Complete Guide to Selling, before filling in order details	Surveying and Specifying			
HOW TO PLACE AN OR ULTRAROOF:	DER FOR	LEFT ELEVATION		RIGHT ELEVATION
 project is existing). Mark and caption the brick piers, windows/or intrusions. Mark the preferred po a) roof windows (vents b) rectangular glazed Upon placement of you 	ohotos of existing drawings if any part of positions of all walls, doors, cut outs / ositions of any s) or velux panels. our Ultraroof order, an generated which must			
NOTES: Please see p29 of Ultrar surveying and specifyin NOT included				

ORDER FORM

JOB REFERENCE



					K O O F	3010110113
ULTRAROOF TILE			METROTILE			
TILE COLOUR			METROTILE	COLOUR		
Carbon grey	Harvest brown	Terra brick	Charcoa	Ebony	Burnt umber Anti	que red
RIDGE / CAPS COI	OUR		RIDGE / CAP	S COLOUR		
Grey	Red Brown		🗌 Grey	Red [Burnt umber	
GUTTER						
U White	Black 🗌 Grey	🗌 Brown 🗌 Ca	aramel			
SOFFIT						
White	Black 🗌 Grey	Rosewood	Light Oak			
DOWNPIPE				CORNICE (Cur	rved ONLY)	
Round	Square			Yes	Grey White	
U White	Black Grey	Brown Ca	aramel			
FRAME STIFFENE	R (Always supplied* on g	able roofs, recommend on	lean-to's above doo	r sets - please conf	firm frame colour)	
🗌 Yes 🗌 No	o Internal colo	ur E	external colour			
(if design needs one,	LLOWS BRACKET FOI check survey guide) 	R BOX BEAM		lease confirm fram	e colour) re any doors in the gable.	
GLASS OPTIONS -					Good Thermal Efficiency	
Low Solar Gain	Super Energy Saving G Medium Solar Ga			Low Solar Gain	Medium Solar Gain	High Solar Gain
	Bronze 4S	Clear 4S		Std Aqua	Std Bronze	Std Clear
Aqua 4S	Blue 4S	olcal 40			Std Blue	Stablear
	Neutral 4S				Std Neutral	
VELUX ROOF WIN Please indicate posit	IDOW (Velux windows no ions on plan. NOTE: Ensur	ot supplied. Velux products re a Velux EDL flashing kit i	s not included in pric is ordered for each V	e) 'elux window (not sı	upplied).	
CK01	🗌 СК02		CK04	ļ	🗌 СК06	
ROOF VENTS ANI	D MECHANISM (mark)	olan)				
Roof vent up t	o ridge R	oof vent with glass abov	ve			
Brass	Manual Spin	dle 🗌 Man	ual Spindle and po	ole 🗌 Manua	al Spindle and telescopic pole	
Chrome	Manual Spin	dle 🗌 Man	ual Spindle and po	le		
Electric motor	r with digital thermosta r with radio and remote	e control	_	or and rocker swi or with thermosta		
Electric witho	ut switch/thermostat (Motor only)				

ANCILLARY EXTRAS

The installer is responsible for ensuring that where Ultraroof is supported by means such as masonry or timber/ PVCu frame walls, the structure provides enough lateral support and resistance to wind uplift. Further guidance can be obtained through Ultraroof's technical documentation/guides. Wendland is not responsible for the structural adequacy of any existing building work used as part of an overall project. Whilst assistance is provided ultimate responsibility for securing Building Regulations lies with the retail installer.

For further guidance please contact the Technical Support Team on 01200 452918 or email techsupport@wendland.uk.com

Job No. 3598 / Page 2 of 6



JOB REFERENCE



Ultraroof on frames

40mm soffit 151.5mm soffit 207.5 14 207.5 172.5 151.3 **Brick & Block** hup! Brick & Block hup!

Ultraroof on walls


72.5mm soffit 251.5 128.5 251.5 14

128.5 14

Brick & Block

hup!

Large soffits





Brick & Block

hup!

Boundary wall options - Brick & block only



Job No. 3598 / Page 3 of 6

Order Form



Tick this box if you would like to order hup! walls with your roof

hup! Wall Specification:

1. Footprint

Please draw the footprint of your building marking each elevation A, B, C, D etc. You should use the base datum which lines up with the external of the Ultrapanel clips - wall finishes and battens will overhang the base. See specification guide for more details.

|
 |
|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | |
 |
 | |
 |
| | | | |
 |
 | | | | | |
 | | |
 |
| | | | | | | | | | | | | | |
 |
| | | | | | | | | | | |
 | | | |
| | | | | | | | | | | | | | |
 |
| | | | | | | | | | | |
 |
 | |
 |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | |
 | | | |
| | | | |
 |
 | | |
 |
 |
 |
 |
 | |
 |
| | | | | | | | | | | |
 | | |
 |
| | | | | |
 | | |
 | |
 |
 |
 | |
 |
| | | | | |
 | | |
 | |
 |
 |
 | |
 |
| | | | | | | | | | |
 |
 |
 | |
 |
| | | | | | | | | | | |
 |
 | |
 |
| | | | | | | | | | | | | | |
 |
| | | | | | | | | | | | | | |
 |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | |
 | | |
| | | | | | | | | | | | |
 | | |
| | | | | | | | | | | | | | | |

Extended Base Tray required?

Width of Cavity wall 300mm. See page 34 of Specification Guide for more details

Please note hup! walls will protrude at least 45mm (25mm for battens, plus c15mm depending on claddings) outside of your base so that the wall finishes (claddings) will be ventilated. All critical dimensions will be confirmed before order stage.

Please return to quotes@ultraframe.co.uk

Order Form



2. Elevations

Please draw each elevation of your hup! walls marking the elevations clearly with A, B, C, D etc. Include window and doors sizes and distance from the eaves as well as the floor clearly.

Tick this box if you require the cable management panel which is supplied on all panels above 560mm.

Order Form



																	 	 	 ,	
3. Wa	all Fi	nich	Dec																	

wall Finishes

Depending on the wall finish can change the sequence of the battens and calcium silicate board, please tick the wall finish for this project?

Brick Mesh	Brick Slips	Render	External Cladding - Type
Brieferfiedh	Brieft enpo	Ronaoi	External oldading Type imminute

4. Walling kit

Please tick the box to confirm which elements of the walling kit you will require to be supplied by Ultraframe.

None - I am supplying my own Ventilation trim only Aperture trim only Batten kit (includes battens and fixi Render Board kit (includes ventilation aperture trims and battens) Brick Mesh (includes trims, battens render board)	on trim, Terracotta/Medium mortar Multi Red/Medium mortar and Mult Orange/Medium mortar	Multi Buff/Light mortar Warm Buff/Light mortar Terracotta/Light mortar Multi Red/Light mortar Mult Orange/Light mortar Grey Brick/Grey mortar
5. Aperture Trim Colour	Grey Brick/Light mortar	
White Smooth G	Grey Light Oak Ro	osewood

Surveyor's Details

For the next 6 months, we will discuss every hup! order with the surveyor to ensure that it has been specified correctly, and therefore, avoid any potential errors on site. Please include your surveyor's details below.

NAME:

CONTACT NO:

EMAIL ADDRESS: