

Glass Roof Order Form



ORDER e: rooforders@wendland.uk.com

QUOTE e: rooforders@wendland.uk.com

New Build

Replacement Project

PLAN VIEW

ACCOUNT No

Company Name

Order Number

JOB REFERENCE

Installer Company Name

Company Contact

Telephone No

Email

Delivery Address

FRONT ELEVATION

POSTCODE

Delivery Date Req

Quotation Ref

CRITICAL INFORMATION

*Required for structural snow / wind loading

*Site Postcode

Site Address**

**Required for any off mainland UK installations

Roof Pitch (°)

Roof height restriction

Frame width

CUSTOMER NOTE: Please carefully read the installation guide before filling in order details.

LEFT ELEVATION

RIGHT ELEVATION

HOW TO PLACE AN ORDER FOR GLASS ROOF:

1. Sketch plan & elevations.
(If necessary, attach photos of existing property. Indicate on drawings if any part of project is existing).
2. Mark and caption the positions of all walls, brick piers, windows/doors, cut outs / intrusions.
3. Mark the preferred positions of any
a) roof windows
4. Upon placement of your Wendland roof order, an order confirmation is generated which must be signed and emailed back.

In order to pass building regulations, all conservatory over 2.5m wide will need a glass U-value of at least 1.2. Smaller conservatories will need glass to be specified with 1.0 U-value. The thermal design guide within UDesign will provide the specific U-Value of each glass roof. **Job No.3598**

Please sign and return to
rooforders@wendland.uk.com

SIGNED

DATE

Glass Roof Order Form



JOB REFERENCE

ROOF COLOUR White (RAL9003) Deeplas (SC050E) Grey (RAL7016) Golden Oak (RAL8003) Rosewood (RAL8017) Black Bespoke RAL/BS Colour

External

Internal

INTERNAL PELMET

Specify with this order Upgrade with retro fit Standard Width (300-600mm) Other (600-1200mm)

Original roof job no. if applicable: Please state (mm):

ROOF INFORMATION (INTERNAL PELMET)

On Fascia* Below Fascia Full Height Walls

If fitting to a bungalow please indicate Soffit Depth
N.B. If order is retro fit then option of **on fascia** is the only option available.

GUTTER COVER - CURVED

Colour Cream White Grey RAL/BS Colour

TIE BARS

White Tie Bar Brass

TOP CAPPINGS

Chambered
Standard
Square (Square only available on Lean To's)

EAVES BEAM

Standard
Gable beam
Bi-fold support beam
Eaves Super bolster
Combined bolstered eaves

OPTIONS

Eaves flow (eaves beam trickle ventilation)
Dentil moulding - clip in
Dentil moulding - adhesive
Dentil packer 60mm frame
Dentil packer 70mm frame

BOX GUTTER OPTIONS

165mm Box Gutter
265mm Box Gutter
165mm Chambered Box Gutter
Reinforced Box Gutter
Other, please state:

GLASS OPTIONS - WARM EDGE SPACER

Super Energy Saving Glass			
Low Solar Gain	Medium Solar Gain	High Solar Gain	Low Solar Gain
Ultimate Blue	Bronze 4S	Clear 4S	Std Aqua
Aqua 4S	Blue 4S		
	Neutral 4S		

Good Thermal Efficiency	
Medium Solar Gain	High Solar Gain
Std Bronze	Std Clear
Std Blue	
Std Neutral	

POLYCARBONATE

Size 25mm 32mm (only available on Chambered cappings)

Colour Clear Opal Bronze Bronze / Opal Heatguard / Opal

UNGLAZED

Polycarb 25mm 32mm (only available on Chambered cappings)

Glass 24mm

ROTABOND SEALANT - MS POLYMER

White (NCGS001W) Black (NCGS001B) No. Tubes Req: N.B. For use with Conservaglass

ROOF VENTS AND MECHANISM (mark plan)

Roof vent up to ridge Roof vent with glass above

Brass Manual Spindle Manual Spindle and pole Manual Spindle and telescopic pole

Chrome Manual Spindle Manual Spindle and pole

Electric motor with digital thermostat and rain sensor Electric motor and rocker switch

Electric motor with radio and remote control Electric motor with thermostat (AVTD002)

Electric without switch/thermostat (Motor only)

SUPPORT BRACKETS

Gallow Bracket How Many?

Hanging Bracket How Many?

Custom Gallow Bracket How Many?

DECORATION

Cresting and finial

ANCILLARY EXTRAS

Job No.3598

Please sign and return to
rooforders@wendland.uk.com

SIGNED

DATE

Order Form

Site postcode must be supplied

1. Base

Are you using the hup! Base? Yes (please supply site photos) No

If yes, please answer the questions below:

Is there a screed? Yes No (min 75mm screed)

What height is the base DPC to ground?

If you have a sloping skirt, please draw it on the diagram, giving a measurement every metre.

Base Insulation type: 100mm insulation (England/Wales) 120mm insulation (Scotland)

Which foundations will you be using? Concrete pads Ground screws pile Supplier

If using ground screws pile, have you completed your ground test before ordering. Yes No

Are there any drain runs within the foot print of the new base?

Which skirt finish do you require? Plain Brick slips (brick type) Brick slips with rails to ground


If you would like brick slips, please let us know the brick type and mortar colour.

Brick type Red Multi Smooth Anthracite Smooth Red Rustic Buff Multi

Mortar colour Grey Sand Red

Are there any drain runs within the foot print of the new base? Yes No Please supply details of their position on your plans

hup! Base DPC to ground level dimension required



2. Datum / plan size

Please draw the footprint of your building marking each elevation A, B, C, D etc. Tick the box to indicate which dimension you are using, indicate a set out point of your plan.

Existing / Traditional base size

Finished wall size

hup! base size (to edge of hup! clips)

Mark intrusions details: drains, pipes and intrusions.

Grid area for drawing the footprint of the building and marking intrusions details.

If you are within 500mm on a boundary line you may need to use our wall hinge system Yes No - see page 12 of the install guide

Please indicate how far the boundary line is from the new extension.

Extended Base Tray required?

Width of Cavity wall 300mm. See hup! Specification Guide for more details.

Please note hup! walls will protrude at least 45mm (25mm for battens, plus c15mm depending on claddings) outside of your base so that the wall finishes (claddings) will be ventilated. All critical dimensions will be confirmed (before order stage on order confirmation).

Please return to hupteam@ultraframe.co.uk

Order Form



2. Elevations

Please draw each elevation of your hup! walls marking the elevations clearly with A, B, C, D etc. Include window and doors sizes and distance from the eaves as well as the floor clearly.

Tick this box if you require the cable management panel which is supplied on all panels above 560mm.

hup! on existing wall

Is hup! going on a existing wall?	Yes	No	If yes, ensure you draw on existing walls, position and height
-----------------------------------	-----	----	--

What is the overall thickness of existing cavity wall?.....mm (internal to external)

Do you want it on cill or full clad? Cill (use internal frame dimension) Full Clad (use external base dimension)

If on cill, please send over **ONLY** the internal frame dimension. If using full clad, please send over **ONLY** the external base dimensions, pages 34-36. .

Ensure you draw the full elevation including existing walls.

This image shows a full page of dot grid paper. The background is white, and it is covered with a regular pattern of small, dark grey dots. The dots are arranged in a precise square grid, with equal spacing between them both horizontally and vertically. This type of paper is commonly used for sketching, journaling, and organizing notes.

Order Form

.....

3. Wall Finishes

The type of wall finish can change the sequence of the battens and calcium silicate board, please tick the wall finish for this project?

Brick Slips Steel façade (Boundary only) Render External Cladding - Type & Thickness

Brick Slips :

Ultraframe to supply: Yes Brick thickness..... Brick Shade: (See hupbrickslips.co.uk for details and prices).....
Mortar Colour: White Neutral Grey None Please note if supplying your own brick slips a lime based mortar must be used.
Window reveal detail : Aperture trim Reveal brick slips Reveal bricks and soldier course

4. Walling kit

Please tick the box to confirm which elements of the walling kit you will require to be supplied by Ultraframe.

None - I am supplying my own Ventilation trim only
Aperture trim only Batten kit (includes battens and fixings)
Render Board kit (includes ventilation trim, aperture trims and battens) Aperture Reveal Solider
Brick Slip Rails (includes trims. Brick slips not supplied)

5. Aperture Trim Colour

White Smooth Grey Light Oak Rosewood

Surveyor's Details

If you would like us to liaise with your surveyor on this hup! order, please put contact details below.

NAME:

CONTACT NO:

EMAIL ADDRESS:

Help us to help you

Please review the details below and look to answer as much as possible within this document.

hup! Base section

Datums - Existing base size or external wall finish

Indication of a set out point on the host wall

Indicate the measurement to the boundary line

Has the ground screw test been completed before ordering

Have you obtained build over agreement if applicable before ordering?

If a build over agreement is required please supply water board parameters from the pipe

Confirm location of drains/manhole or that there are none underneath the hup! footprint

Confirm locations of any rear wall obstructions i.e. SVP or gullies

DPC to Ground Measurement

Confirm whether there is sloping ground - See specification for survey details required

Base skirting, brick type, mortar colour

Is there a screed? Min 75mm please state yes or no or tick the box on page 1

If placing hup! on an existing base - have you reviewed the different offsets

hup! Wall section

Boundary wall solution - if you are closer than 500mm please contact Ultraframe for further info

Please consider eaves heights, window and door sizes any obstructions indicated

Wall finish and colour

Brick slip finish - who is supplying?

Brick slip thickness, 14mm, 15mm or 20mm?

Aperture trims or brick reveals

If you are using cladding near a boundary - does it meet fire regulations?

If any walls are less than 800mm high - any opening window may need permanently restriction?

If building hup! on a dwarf wall - state what size the overall cavity wall thickness is

Refer to table in the specification guide for extra insulation requirements

If cladding ask about our steel facade on boundary lines

Roof section

State type of roof

Pitch of roof (note: Flat roof is at 1 degree)

Check the gutter is in not overhanging the neighbour's boundary line

Glass type and colour or unglazed

Does the glass need a muntin bar or oversized glass

Any spans over 4000mm on Ultrarroof

Any spans over 5600mm on Flat Roof

Any elevation over 5800mm check the beam split is supported by a wall / post

Are gallows brackets required - do they need ordering

Hip/Ridge choice (metrotile only)

Fascia and gutter colour

Outlet / downpipe position

Other information to assist us in your order

Site pictures

Building Control - who are you using

Ground screw pile company - who are you using

Do you have enough room for storage on site or is this split delivery - please discuss with Ultraframe

Advise Ultraframe on the room use i.e. gym or hot tub for the correct screw or pad count for a loading report