

Livinroof Order form



☐ **ORDER** e: rooforders@wendland.uk.com

☐ **QUOTE** e: rooforders@wendland.uk.com

☐ New Build ☐ Replacement Project

ROOF U-VALUE: ☐ 0.15 (standard) ☐ 0.12 (thermally enhanced)

PLAN VIEW

ACCOUNT No.

Company Name

Order Number

JOB REFERENCE

Installer Company Name

Company Contact

Telephone No.

Email

Delivery Address

POSTCODE

Delivery Date Req

Quotation Ref

CRITICAL INFORMATION

*Required for structural snow / wind loading

*Site Postcode

Site Address**

**Required for any off mainland UK installations

Roof Pitch (°)

Roof height restriction

Frame width

CUSTOMER NOTE: Please carefully read the Livinroof System Overview Guide before filling in order details.

How to place an order for a Livinroof

1. Fill in above information and sketch plan and elevations showing position and dimensions of walls, brick piers, windows, doors, cut outs and intrusions. If necessary, attach photos of existing property.

2. Advise of the preferred position of any roof vents, rainwater pipes (RWP), tie bars and any additional information that may assist in specifying your order. If a Goalpost is needed, please complete page 3 of this order form.

3. A confirmation drawing will be created using our bespoke software and sent to you via email for you to check and sign. This will start the manufacture process. A delivery date will be emailed back as soon as it is scheduled.

Wendland are committed to not only offering the very best products but the best Customer Service experience. If you have any questions, queries or concerns please feel free to contact us on 01200 452 904 or email us on rooforders@wendland.uk.com and we will help any way we can.

If you have a technical question relating to our products, please contact our technical team on 01200 452 918 or email us on techsupport@wendland.uk.com

You can also find technical help or any of our product literature on our website <https://www.wendland.uk.com/trade-downloads/>

FRONT ELEVATION

LEFT ELEVATION

Livinroof Order form



JOB REFERENCE

ROOF INFORMATION

☐ On Fascia ☐ Below Fascia* ☐ Full Height Walls

If fitting to a bungalow please indicate Soffit Depth

*N.B. **Below fascia** is always on boxgutters, 30mm frame add on is needed but not supplied.

INTERNAL PELMET

☐ Specify with this order ☐ Upgrade with retro fit ☐ Standard Width (300-600mm)

Original roof job no. if applicable:

EXTERNAL PANEL

☐ U-Tec through colour composite (to match 7016) ☐ Aluminium powder coated sandwich (to match 7016)

CORNICE

Style ☐ 1 Tier ☐ 2 Tier ☐ 3 Tier ☐ Curved

Colour ☐ White ☐ Urban Grey ☐ Deeplas White ☐ Landmark Green ☐ Pure Cream ☐ RAL/BS Colour
RAL 9003, RAL 7016, INTERPON SC050E, BS14C35, RAL 1015, ☐ Gloss %
GLOSS 80% GLOSS 30% GLOSS 80% GLOSS 80% GLOSS 30%

BOX GUTTER OPTIONS:

☐ 165mm Box Gutter ☐ 265mm Box Gutter ☐ 165mm Chambered Box Gutter ☐ Reinforced Box Gutter ☐ Other, please state:

GLASS OPTIONS - WARM EDGE SPACER

Super Energy Saving Glass

Low Solar Gain	Medium Solar Gain	High Solar Gain
☐ Ultimate Blue	☐ Bronze 4S	☐ Clear 4S
☐ Aqua 4S	☐ Blue 4S	
	☐ Neutral 4S	

Good Thermal Efficiency

Low Solar Gain	Medium Solar Gain	High Solar Gain
☐ Std Aqua	☐ Std Bronze	☐ Std Clear
	☐ Std Blue	
	☐ Std Neutral	

ROTABOND SEALANT - MS POLYMER

☐ Black Tubes (NCGS001B)

Downpipe

☐ Round
☐ Square

CONSERVAFLASH

☐ Soaker Only
☐ Yes

ROOF VENTS AND MECHANISM (mark plan)

☐ Roof vent with glass above

Brass ☐ Manual Spindle ☐ Manual Spindle and pole ☐ Manual Spindle and telescopic pole
Chrome ☐ Manual Spindle ☐ Manual Spindle and pole

☐ Electric motor with digital thermostat and rain sensor ☐ Electric motor and rocker switch
☐ Electric motor with radio and remote control ☐ Electric motor with thermostat (AVTD002)
☐ Electric without switch/thermostat (Motor only)

ANCILLARY EXTRAS

Please refer to the Livinroof Technical Guide.

IMPORTANT NOTE 1

The installer is responsible for ensuring that where Livinroof is supported by means such as timber/PVCu frame walls, the structure provides enough lateral support and resistance to wind uplift. Further guidance can be obtained through our system overview. Wendland cannot be responsible for the structural adequacy of any existing building work used as part of an overall conversion. While assistance is provided, ultimate responsibility to secure Building Regulations / approvals lies with the retail installer.

IMPORTANT NOTE 2

U-Design is the final arbiter on price and specification decisions.

IMPORTANT NOTE 3

The Livinroof components have been designed and manufactured to meet the specification of each individual job. Any significant on site modifications particularly relating to the repositioning of any structural members will invalidate the product's warranty and compromise the structures integrity. If adjustments are required due to site conditions please consult Wendland. Tie Bars / Tie Beams will be specified by Wendland and will appear on your confirmation. Always check the confirmation carefully.

Goalpost specification

Goalpost Colour

☐ To match roof internals


☐ Bespoke:- RAL colour

Leg length

Frame height

Length below floor/cill

Goalpost leg example



Disclaimer:

Wendland does not take responsibility for the structural stability of the entire structure, only the products provided by Wendland. To ensure the rest of the structure is suitable, it is the installers responsibility to ensure that all walls, foundations and building structure are compliant with Document A of Building Regulations. Any adjoining window frames must be a minimum of 70mm reinforced PVC frames, coupled in accordance with the manufacturer's recommendations. Host walls must be suitable to take the additional load and forces of the new building.

All beam end plates (WP and SP) must be bolted to a suitable substrate with adequate anchors. For the WP, the host wall suitability to accept the increased forces must be checked. The SP should be positioned on a suitable concrete padstone built into the supporting wall and strapped down to at least two additional courses.

Baseplates must be anchored using a minimum of 3no. M12 through bolts (minimum 6kN Tension/Uplift capacity per bolt). Foundations or floor slabs must be designed to accept the additional forces.

Order Form

Site postcode must be supplied

1. Base

Are you using the hup! Base? ☐ Yes (please supply site photos) ☐ No

If yes, please answer the questions below:

Is there a screed? ☐ Yes ☐ No (min 75mm screed)

What height is the base DPC to ground?

If you have a sloping skirt, please draw it on the diagram, giving a measurement every metre.

Base Insulation type: ☐ 100mm insulation (England/Wales) ☐ 120mm insulation (Scotland)

Which foundations will you be using? ☐ Concrete pads ☐ Ground screws pile ☐ Supplier

If using ground screws pile, have you completed your ground test before ordering. ☐ Yes ☐ No


Which skirt finish do you require? ☐ Plain ☐ Brick slips (brick type) ☐ Brick slips with rails to ground

If you would like brick slips, please let us know the brick type and mortar colour.

Brick type ☐ Red Multi ☐ Smooth Anthracite ☐ Smooth Red ☐ Rustic Buff Multi

Mortar colour ☐ Grey ☐ Sand ☐ Red

Are there any drain runs within the foot print of the new base? ☐ Yes ☐ No Please supply details of their position on your plans



2. Datum / plan size

Please draw the footprint of your building marking each elevation A, B, C, D etc. Tick the box to indicate which dimension you are using, indicate a set out point of your plan.

☐ Existing / Traditional base size ☐ Finished wall size ☐ hup! base size (to edge of hup! clips)

Mark intrusions details: drains, pipes and intrusions.

Grid area for drawing the footprint of the building and marking intrusions.

If you are within 500mm on a boundary line you may need to use our wall hinge system ☐ Yes ☐ No - see page 12 of the install guide

Please indicate how far the boundary line is from the new extension.

Extended Base Tray required? ☐

Width of Cavity wall 300mm. See hup! Specification Guide for more details.

Please note hup! walls will protrude at least 45mm (25mm for battens, plus c15mm depending on claddings) outside of your base so that the wall finishes (claddings) will be ventilated. All critical dimensions will be confirmed (before order stage on order confirmation).

Please return to hupteam@ultraframe.co.uk

Order Form



2. Elevations

Please draw each elevation of your hup! walls marking the elevations clearly with A, B, C, D etc. Include window and doors sizes and distance from the eaves as well as the floor clearly.

Tick this box if you require the cable management panel which is supplied on all panels above 560mm. ☐

hup! on existing wall

Is hup! going on a existing wall? ☐ Yes ☐ No If yes, ensure you draw on existing walls, position and height

What is the overall thickness of existing cavity wall?.....mm (internal to external)

Do you want it on cill or full clad? ☐ Cill (use internal frame dimension) ☐ Full Clad (use external base dimension)

If on cill, please send over **ONLY** the internal frame dimension. If using full clad, please send over **ONLY** the external base dimensions, pages 34-36. .

Ensure you draw the full elevation including existing walls.

[illegible]

Order Form

.....

3. Wall Finishes

The type of wall finish can change the sequence of the battens and calcium silicate board, please tick the wall finish for this project?

☐ Brick Slips ☐ Steel façade (Boundary only) ☐ Render ☐ External Cladding - Type & Thickness

Brick Slips :

Ultraframe to supply: ☐ Yes Brick thickness..... Brick Shade: (See hupbrickslips.co.uk for details and prices).....

Mortar Colour: ☐ White ☐ Neutral Grey ☐ None Please note if supplying your own brick slips a lime based mortar must be used.

Window reveal detail : ☐ Aperture trim ☐ Reveal brick slips ☐ Reveal bricks and soldier course

4. Walling kit

Please tick the box to confirm which elements of the walling kit you will require to be supplied by Ultraframe.

☐ None - I am supplying my own ☐ Ventilation trim only
☐ Aperture trim only ☐ Batten kit (includes battens and fixings)
☐ Render Board kit (includes ventilation trim, aperture trims and battens) ☐ Aperture ☐ Reveal ☐ Solider
☐ Brick Slip Rails (includes trims. Brick slips not supplied)

5. Aperture Trim Colour

☐ White ☐ Smooth Grey ☐ Light Oak ☐ Rosewood

Surveyor's Details

If you would like us to liaise with your surveyor on this hup! order, please put contact details below.

NAME:

CONTACT NO:

EMAIL ADDRESS:

Help us to help you

Please review the details below and look to answer as much as possible within this document.

hup! Base section

- ☐ Datums - Existing base size or external wall finish
- ☐ Indication of a set out point on the host wall
- ☐ Indicate the measurement to the boundary line
- ☐ Has the ground screw test been completed before ordering
- ☐ Have you obtained build over agreement if applicable before ordering?
- ☐ If a build over agreement is required please supply water board parameters from the pipe
- ☐ Confirm location of drains/manhole or that there are none underneath the hup! footprint
- ☐ Confirm locations of any rear wall obstructions i.e. SVP or gullies
- ☐ DPC to Ground Measurement
- ☐ Confirm whether there is sloping ground - See specification for survey details required
- ☐ Base skirting, brick type, mortar colour
- ☐ Is there a screed? Min 75mm please state yes or no or tick the box on page 1
- ☐ If placing hup! on an existing base - have you reviewed the different offsets

hup! Wall section

- ☐ Boundary wall solution - if you are closer than 500mm please contact Ultraframe for further info
- ☐ Please consider eaves heights, window and door sizes any obstructions indicated
- ☐ Wall finish and colour
- ☐ Brick slip finish - who is supplying?
- ☐ Brick slip thickness, 14mm, 15mm or 20mm?
- ☐ Aperture trims or brick reveals
- ☐ If you are using cladding near a boundary - does it meet fire regulations?
- ☐ If any walls are less than 800mm high - any opening window may need permanently restriction?
- ☐ If building hup! on a dwarf wall - state what size the overall cavity wall thickness is
- ☐ Refer to table in the specification guide for extra insulation requirements
- ☐ If cladding ask about our steel facade on boundary lines

Roof section

- ☐ State type of roof
- ☐ Pitch of roof (note: Flat roof is at 1 degree)
- ☐ Check the gutter is in not overhanging the neighbour's boundary line
- ☐ Glass type and colour or unglazed
- ☐ Does the glass need a muntin bar or oversized glass
- ☐ Any spans over 4000mm on Ultraroom
- ☐ Any spans over 5600mm on Flat Roof
- ☐ Any elevation over 5800mm check the beam split is supported by a wall / post
- ☐ Are gallows brackets required - do they need ordering
- ☐ Hip/Ridge choice (metrotile only)
- ☐ Fascia and gutter colour
- ☐ Outlet / downpipe position

Other information to assist us in your order

- ☐ Site pictures
- ☐ Building Control - who are you using
- ☐ Ground screw pile company - who are you using
- ☐ Do you have enough room for storage on site or is this split delivery - please discuss with Ultraframe
- ☐ Advise Ultraframe on the room use i.e. gym or hot tub for the correct screw or pad count for a loading report